

42 Draft Designs

Jetta IV, Golf IV Bumper Sidemarker Installation Instructions

1. Remove the stock amber bumper marker by pushing in on the rectangular side, and sliding the entire light towards the front of the car. This will release the two alignment tabs located in the front of the lights. When they are released, pull out the entire assembly.
2. Remove the bulb holder by pulling straight off. It may take some force, but **do not twist** the bulb holder. Twisting the bulb holder will break the two inner tabs of the stock light. They are not important, but breaking them will result in plastic being stuck in the bulb holder.
3. If replacing your light bulbs, remove the stock 194 light bulb by pulling it straight out of the socket. Replace the bulb with colored units of your choice by pushing the wedged end into the corresponding tabs. Install bulb holder on new light by pushing onto the circular portion of the light. Note the final location of the black plastic clip and bulb holder as indicated by the holes in the bumper strip.
4. Fit the new bumper marker by inserting the black plastic clip into its final location and pushing in the rectangular side of the light. With the front of the lamp pushed in, slide the light towards the front of the car and position the two alignment tabs on the rear of the light. Release the square end of the light and the entire unit should pop into place!

Please note: the stock light bulbs and amber bulbs sold by 42 are of suitable wattage and burn low temperature. We are not responsible for problems attributed to improper bulb wattage. Popular low quality "hyperwhite" 194 light bulbs are rated to burn higher wattage and often produce temperatures capable of melting most plastics. Use at your own risk.

Warning: Failure to push bulb holder onto the backing far enough will result in melted lights! Note how far the bulb holder installs on the OEM backings and be sure to install exactly on your new lights. We are not responsible for melting due to improper bulb holder installation.

42 Draft Designs

Jetta IV, Golf IV Bumper Sidemarker Installation Instructions

1. Remove the stock amber bumper marker by pushing in on the rectangular side, and sliding the entire light towards the front of the car. This will release the two alignment tabs located in the front of the lights. When they are released, pull out the entire assembly.
2. Remove the bulb holder by pulling straight off. It may take some force, but **do not twist** the bulb holder. Twisting the bulb holder will break the two inner tabs of the stock light. They are not important, but breaking them will result in plastic being stuck in the bulb holder.
3. If replacing your light bulbs, remove the stock 194 light bulb by pulling it straight out of the socket. Replace the bulb with colored units of your choice by pushing the wedged end into the corresponding tabs. Install bulb holder on new light by pushing onto the circular portion of the light. Note the final location of the black plastic clip and bulb holder as indicated by the holes in the bumper strip.
4. Fit the new bumper marker by inserting the black plastic clip into its final location and pushing in the rectangular side of the light. With the front of the lamp pushed in, slide the light towards the front of the car and position the two alignment tabs on the rear of the light. Release the square end of the light and the entire unit should pop into place!

Please note that the stock light bulbs or amber bulbs sold by 42 are of suitable wattage and burn low temperature. We are not responsible for problems attributed to improper bulb wattage. Popular low quality "hyperwhite" 194 light bulbs are rated to burn higher wattage and often produce temperatures capable of melting most plastics. Use at your own risk.

Warning: Failure to push bulb holder onto the backing far enough will result in melted lights! Note how far the bulb holder installs on the OEM backings and be sure to install exactly on your new lights. We are not responsible for melting due to improper bulb holder installation.